

**XC125 BELUGA**

**YAMAHA**



## You'll never want to walk, ride the bus or take the train again.

That's because once you experience how much fun riding a Yamaha XC125 scooter can be, you'll never rely on public transportation again.

Whether you're headed uptown, downtown or crosstown, the XC125 does it with style and ease. It's powered by a four-stroke SOHC two-valve engine, and cooled by an integral fan. The XC125 uses a push-button electric starter, auto choke and V-belt automatic transmission to make your riding experience smooth and hassle free.


To make riding the XC125 even more pleasant we've included a deeply padded stepped seat, cushioned passenger handgrips, a wide apron and wider tyres.

What more could you want from a scooter?

How about a rear-wheel foot brake, a locking glove compartment and sharp looking colours.

We think you'll agree, after taking a ride on the XC125, you'll never want to walk, ride the bus or take the train again!





A rectangular 12V 45/40 watt headlamp gives excellent night time vision. Large handlebar cowling and leg shields keep the elements away from the rider.



Full instrumentation includes a fuel gauge, a speedometer plus turn signal and oil level indicator lamps for easy to read rider information.



Built into the front of the XC125 is a convenient front trunk. It's handy for carrying small items, and can be locked with a key for added security.



Sturdy steel-tube rear rack for carrying your briefcase, books or shopping.



#### XC125 TECHNICAL SPECIFICATIONS

<b>Engine</b>		<b>Chassis</b>	
Type .....	single cylinder, 4-stroke, SOHC, air-cooled	Overall length .....	1.895 mm
Displacement .....	124 cc	Overall width .....	650 mm
Bore & stroke .....	49 x 66 mm	Overall height .....	1.095 mm
Compression ratio .....	9,5 : 1	Seat height .....	760 mm
Max. power (DIN) .....	8.7 PS @ 8,000 rpm	Wheelbase .....	1.250 mm
(ISO) .....	6.4 kW @ 8,000 rpm	Min. ground clearance .....	110 mm
Max. torque (DIN) .....	0.9 kg/m @ 6,500 rpm	Dry weight .....	99 kg
(ISO) .....	8.8 Nm @ 6,500 rpm	Suspension Front .....	Bottom link fork
Ignition .....	T.C.I.	Suspension Rear .....	Unit swing
Starter system .....	Electric	Brake Front .....	Drum
Fuel tank capacity .....	7 litres	Brake Rear .....	Drum
Oil capacity .....	1.1 litres	Tyre Front .....	100/90-10 56J
Transmission .....	Single speed automatic	Tyre Rear .....	100/90-10-56J
Final transmission .....	V-belt		

Always wear a helmet, eye protection and protective clothing. Yamaha encourage you to ride safely and respect fellow riders and the environment. Specifications and appearance of Yamaha products shown here may vary according to requirements and conditions, and are subject to change without notice.

For further details, please consult your Yamaha dealer.

HALLMAN & ENEQVIST MOTOR AB  
BOX 600, 136 26 HANINGE  
TELEFON 0750-124 40.

Sköt din Yamaha med

**Mobil**

Vinnarnas oljeprogram

**MotorTema**  
Amerikavägen 9 Kalmar  
Tel. 0480-115 65

**YAMAHA**  
YAMAHA MOTOR CO. LTD.  
LTJ-2M2-C10714-90E